



# CLASSIC RAPID SETPLUG

## A Fast Setting Plugging Mortar

### Product:

**Classic Rapid Setplug** is a single part fast setting hydraulic compound that instantly stops flowing water and seepage through concrete and masonry surface.

### Composition:

**Classic Rapid Setplug** is a non-shrink material that expands slightly and sets in approximately 3 minutes depending on the temperature of the mixing water and the surface to which it is applied. It sets under water. It has high structural strength and exceptional durability.

### Uses:

**Classic Rapid Setplug** will stop running water and seepage through cracks and holes in concrete and masonry walls, dams, wells, tanks, walls and floor junctions. It can be used as grout around pipes, conduits and can be used as an anchoring product and a rapid set filler.

### Instruction for Use:

#### Surface Preparation:

Before the application of **Classic Rapid Setplug**, masonry around the hole or crack should be chiselled out to a depth and width not less than 25mm. If areas to be patched are holding water under pressure, weep holes should be made at the base of the wall to relieve pressure.

#### Mixing:

**Classic Rapid Setplug** should be gradually added to clean water and mixed with a small trowel for 45 seconds. Water and Powder should be mixed in the ratio of 1:4 by volume or 1:5 by weight.

#### Priming:

No priming is necessary.

#### Application:

The prepared **Classic Rapid Setplug** is held in a gloved hand until heat generation is felt and

then forced into the crack or void. Hardening will take approximately 3 minutes. After the material has been allowed to harden and no sign of water ingress is visible, it is advisable to overcoat with **Classic Acrybond/ Classic Tankscreed** system

### Curing:

Under normal circumstances or if the material is to be over coated, then no curing is necessary. Under severe drying conditions, the use of a sprayed on curing membrane such as SETCRETE 8 (see appropriate data sheets), wet hessian or polythene sheeting is recommended to prevent rapid drying.

### Storage:

**Classic Rapid Setplug** has a shelf life of 6 months in sealed containers under shade in dry condition.

### Yield:

A 5 Kg bag will yield approximately 2.6 litres.

### Pack:

**Classic Rapid Setplug** range of waterproofing systems should not be placed when the substrate or ambient temperature is 5°C or less. They should be protected from frost. Maximum recommended water quantity should not be used. These products will not suppress rising dampness.

### Variety of Products:

Following are the other similar products from Primadonn Buildtech Pvt. Ltd.

- Classic Acrybond-A
- Classic Acrybond
- Classic Acryfix DP
- Classic Acryfix L
- Classic Acryflex WMC
- Classic Brickseal

# CLASSIC RAPID SETPLUG

A Fast Setting Plugging Mortar

- Classic Crete SBR
- Classic Crystalsys
- Classic Latex SBR-200
- Classic Silcoat
- Classic Silcoat S
- Classic Tankscreed
- Classic Uniseal BU



---

**Primadonn Buildtech Pvt. Ltd.**

(An ISO 9001:2015 Certified Company)

No: 349, RS Road, Srinivasa Nagar, Kavaraipettai, Gummidipoondi, Chennai-601206.

Phone: +91-9514709240

Mail: [support@primadonn.com](mailto:support@primadonn.com)

[www.primadonn.com](http://www.primadonn.com)

