



CLASSIC EPOTM WBE - 381

Water Based Epoxy Coating

Product:

Classic Epo WBE – 381 is a two-part, water based, epoxy coating available in different colours. This coating provides a dustproof cleanable durable sealing coat on cement and concrete surfaces.

Description :

Classic Epo WBE – 381 protective coating is water-based epoxy system which comes in prepacked quantities. The cured film is extremely tough and has a smooth, hard surface. This coating is non toxic in nature. This coating also has an excellent adhesion to concrete and cementitious surfaces, outstanding, chemical resistance and is unaffected by oil, grease, petrol, etc.,

Advantages:

- Resistant to a wide range of chemical and acids.
- Hygienic and easily cleaned.
- Resistant to oil, grease, etc.,
- Excellent adhesion to most.
- Easy to apply.
- Resistant to fungal attack.

Pack & Coverage

1 kg and 5 kg packs. 1 kg pack will cover an approximate area of 3 to 4 sq.mt. for recommended two coats. This will give an overall dry film thickness of 200 microns.

Properties

Colour: Any colour

Pot life (at 30°C): 30 mins

Curing time (at 30°C): 1 day for light foot traffic and 7 days for full chemical resistance.

Where to Use:

- Water tank and sumps
- Retaining Walls.
- Basements and Underground.
- Terrace and Slope roofs.
- Sunken slab
- Roof gardening

Instructions for applying:

Surface Preparation

Surface should be sound, level and free of grease, oil and loose deposits. Vacuum grit blasting or mechanical scabbing techniques are recommended to ensure optimum adhesion.

Mixing:

Taking care to ensure that the bottom and side are thoroughly scrubbed transfer the entire contents of the Classic Epo WBE – 381 hardener and its resin into a mixing bucket and using a jiffy-type mixer attached to a slow-running electric drill, mix for a approximately two minutes.

Application:

Once mixing is complete, transfer the mixer Classic Epo WBE – 381 to roller tray and using medium pile simulated sheepskin in roller, apply evenly over the surface.

CLASSIC EPOTM WBE - 381

Water Based Epoxy Coating

Cleaning:

Equipment should be cleaned with water immediately after use.

Storage Life:

Shelf life is 6 months when stored in manufacturer's undamaged sealed containers under dry conditions and out of direct sun light at temperatures between 5 to 30°C.

Variety of Products:

Following are the other similar products from Primadonn Build Tech Pvt Ltd.,

Classic Acrybond – A
Classic Acrybond
Classic Acryfix DP
Classic Acryfix L
Classic Acryflex WMC
Classic Brickseal
Classic Crete SBR
Classic Crete RMW
Classic Crystalsys
Classic Acryfix SB
Classic Tankscreed
Classic Rapid Setplug
Classic Silcoat
Classic Silcoat S
Classic Uniseal BU

TAMILNADU

Corporate Office

PRIMADONN BUILD TECH PVT LTD

No. 349, First Floor, Srinivasa Nagar, Kavaripeetai, Gummidipoondy 601 206.

Ph.+91-8220513172,

Admin Office:

No.605, Selva Vinayaga Nagar, Grant Lyon Village, Ponneri Tk., Thiruvalluvar Dt., Ph+91-6379174327, +91-8438276059.

Manufacturing Unit

No.603, Selva Vinayaga Nagar, Grant Lyon, Vadagarai, Chennai 600 052. Ph.+91-9444907177

KARNATAKA

Corporate Office:

PRIMADONN CONSTRUCTION CHEMICALS (P) LTD.,

Talacauvery Layout, Basavanagar, Bangalore 560 037. Ph.+9150878429, +91-9345411355.

PONDICHERRY

Branch Office

192/A, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-4208833, 91-+9514709240

Distrubutor's

151, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-2222100, 91-+9345561820

Email: Info@Primadonn.com, www.Primadonn.com

