



PRIMADONN

Buildtech Pvt. Ltd.

DELIVERING INNOVATION WITH EXPERIENCE

An ISO 9001:2015 Registered Company



PROFILE

PRIMADONN Buildtech Pvt. Ltd. offers permanent and long lasting solutions to the construction industry with the result of many year of understanding the needs of the construction industry in India. The product range not only offers upgraded and state of the art construction products, also to cater the civil construction requirements which are a boon in solving even the critical problems in this industry.

Eventhough most of the construction chemical products are time tested in many advanced countries, as well as in India. PRIMADONN has updated these formulations with high intense technologies and giving an edge competitor products in order to emerge as one of the leaders in the field of construction speciality chemicals. While PRIMADONN has a wide range of products to cater the everyday needs to the civil construction industry, it keeps the technology so simple and friendly for the end users and even the unskilled lay person can understand it. The product range of construction chemicals include Admixtures, Waterproofing system, Repairs, Adhesive & Surface Treatment, Industrial Grouts & Flooring, Sealants & Protective Coatings, Eco-friendly & Special Products and Bitumen Products.

PRIMADONN is in the process of joining hands with the leading global technocrafts who provides latest methodologies to solve the construction problems in the most cost efficient with long lasting results as well as the lastest trends in green technology. PRIMADONN is driven by the excited and ambitious team members who have made their remarkable achievements in the construction speciality chemicals and other fields in India through professional and service oriented approach to satisfy even the smallest customer's requirements. The core of PRIMADONN is the customer's satisfaction through value added products with innovative technology.

Formerly Known as

Primadon Construction Products Pvt. Ltd.

Hyderabad



OHSAS 18001 Certified

www.primadonn.com

RANGE OF PRODUCTS

ADMIXTURES

Classic SUPERFLO - N

WATER REDUCER /PLASTICISER, STANDARDS: BS 5075 PART 1 IS 9103 ASTM C - 494 TYPE A

Increases workability with existing mix. Reduces W/C ratio by 8 to 10 % for given workability. Increases strength DOSAGE:150ml - 250ml per 50Kg cement.

Classic SUPERFLO - SP

HIGH RANGE WATER REDUCER (SUPER PLASTICISER) STANDARDS:BS 5075 PART 13 IS 9103 ASTM C 494 TYPE F

Very high workability resulting in high water reduction by 15% to 30%. High quality concrete with accelerated early strength. DOSAGE: 200ml - 750ml per 50Kg cement.

Classic CRETE - RPL

HIGH RANGE WATER REDUCER CUM SLUMP RETAINER (SUPER PLASTICISER) STANDARDS: BS 5075 PART 3 IS 9103 1999 ASTM C-494 TYPE B.D.G

Very high workability. Excellent slump retention with time. Ideal for RMC Plants. High early strength. DOSAGE: 200ml - 600ml per 50Kg cement.

Classic SUPERFLO SPECIAL

HIGH RANGE WATER REDUCER STANDARDS: BS 5075 PART 3 IS 9103 ASTM C-494 TYPE A F

Very high workability. Used for self compacting concrete. High early strength. DOSAGE: 200ml - 1000ml per 50Kg cement.

Classic CRETE - RMW

INTEGRAL WATER PROOFING ADMIXTURE FOR CONCRETE STANDARDS: IS 2645 BS 1881 PART 5

Reduces permeability. Increases workability. Reduces w/c ratio by 8-10% for given workability. More dense water tight concrete and mortar. DOSAGE: 150ml - 200ml per 50Kg cement.

Classic CRETE - RMW (POWDER)

HIGH PERFORMANCE INTEGRAL WATER PROOFING COMPOUND

Economical in application, chloride free hence no effect on concrete. As an effective pore filler. Helps to reduce capillaries and pores to prevent waterseepage. Improves cohesiveness. Minimize shrinkage cracks. DOSAGE: 500 gm per bag of cement.

Classic CRETE - AXL (CF)

CHLORIDE FREE ACCELERATOR AND FROST PROOFER

Quickens the setting time. Increases workability. Makes placing easier for emergency repair works. DOSAGE: 1000ml per bag of cement.

Classic CRETE - AXL (CB)

ACCELERATING ADMIXTURE FOR CONCRETE BLOCKS

Quickens the setting time. Increases workability. Makes placing easier for emergency repair works. DOSAGE: 600ml - 1000ml per bag cement.

Classic CRETE AIRENT

AIR ENTRAINING PLASTICISER

Introduces air entrainment in concrete without loss in strength. Better surface finish. Can be used with m-sand. DOSAGE: 100ml -160ml per bag of cement.

Classic MORTAR PLASTICISER

HIGH RANGE MORTAR PLASTICISER STANDARDS: BS 4887 PART 1

High workability. Gives smooth, creamy mortar even with harsh sand. Reduces shrinkage cracks. Increases mortar yield by 10-20%. DOSAGE: 100ml - 300ml per bag of cement.

Classic SUPERFLO - PC

POLYCARBOXYLATE BASED SUPER PLASTICISER FOR HIGH PERFORMANCE CONCRETE

High workability, High early and ultimate strength. Used for precast concrete. COVERAGE: 200ml - 800ml per 50 Kg bag of cement.

Classic POLY - PROPYLENE FIBRES

SYNTHETIC POLY PROPYLENE FIBRES FOR CONSTRUCTION

Easy dispersion in the mix. Crack inhibition. Increased tensile strength. Decreases water permeability, Less wastage. Nontoxic, Environmental friendly. DOSAGE: 125g per 50 Kg cement.

Classic PLASTO - MASTER

HIGH RANGE MORTAR PLASTICISER

Crack Inhibition, Increased tensile strength. Can be mixed with M-Sand and Query dust. DOSAGE: 100ml to 200ml per bag of cement.

WATER PROOFING SYSTEM

Classic RAPID SETPLUG

RAPID SET PLUGGING MORTAR

Fast setting hydraulic compound which instantly stops gushing water or seepages.

Classic CRYSTALSYS

SINGLE COMPONENT CEMENTITIOUS WATERPROOF COATING

Excellent bonding, durability and water tightness. Blocks the capillaries in the substrate. Allows surface to breathe. COVERAGE: 25Kg + 8 to 9 liters water covers 16-25 Sq. m. 2 or 3 coats.

Classic ACRYBOND

TWO PART ACRYLIC MODIFIED CEMENTITIOUS WATER PROOF COATING STANDARDS: ASTM D 4060 & D 412

Excellent bonding, durability and water tightness. Elastic, allows some movement Allows surface to breathe. Resists wear and tear. Abrasion resistant to light foot traffic. Forms an impermeable membrane. Fibre reinforced for anticrack property. COVERAGE: 20 Kg pack covers 15 to 18 Sq.m. For 2 coats 10 Kg pack covers 7 to 9 Sq.m.

Classic ACRYBOND - A

TWO PART ACRYLIC MODIFIED CEMENTITIOUS WATERPROOF COAT-

Excellent bonding, durability and water tightness with large amount of packing. Resists wear and tear. Forms an impermeable membrane. COVERAGE: 28 Kg pack covers 18 to 20 Sq.m. For 2 coats 14 Kg pack covers 10 to 12 Sq.m.

Classic TANKSCREED

TROWEL APPLIED WATER PROOFING

Waterproofing mortar for tanks where hydrostatic pressure exists. Fibre reinforced for anti-crack property. COVERAGE: 25 Kg+5.0 to 5.5 litre water covers 2.6 Sq. m. per coat. 1 to 2 coats are recommended.

Classic BRICKSEAL

SINGLE COMPONENT CEMENTITIOUS WATER PROOFING RENDER

Gives excellent water proofing property for brickwork and other substrate with low free lime content. Excellent adhesion. Allows surface to breathe. COVERAGE: 25 Kg + 8 to 9 Liter water covers 8 to 9 Sq.mt.

Classic ACRYFLEX WMC

SINGLE COMPONENT SEAMLESS WATER PROOFING ELASTOMERIC MEMBRANE

Excellent bonding with the substrate Allows movement. Forms an impermeable flexible membrane with high adhesive properties. COVERAGE: 5 Kg covers 9 to 11 Sq.m.

Classic CRETE - SBR

STYRENE PUTADIENE RUBBER LATEX, FLOOR HARDENER, POLYMER LATEX AND BONDING AGENT FOR CEMENTITIOUS MIX.

Excellent bonding with most building materials. Outstanding water resistant. Good chemical/ Salt resistant. Increases flexibility. COVERAGE: For bond coat 1:1 water 3 to 4 Kg of cement will covers approx 4 to 6 Sq.mt.

Classic LATEX SBR - 200

POLYMER LATEX, FLOOR HARDENER AND WATER PROOFING ADMIXTURE.

Excellent bonding with most building material. COVERAGE: 500 ml to 1 Lt. per bag of cement as a floor hardener, 100 ml to 200 ml for normal plastering.

Classic ACRYFIX - SB

WATERPROOF ACRYLIC MODIFIER AND BONDING AGENT

Outstanding water resistant with high bonding property. Increases flexibility. COVERAGE: For bond coat 1:500ml water 3 to 4 Kg of cement will covers approx. 3 to 4 Sq.m; For polymer concrete 10 to 12 Lt. per bag of cement; For normal plastering 100 ml per bag of cement.

Classic ACRYFIX - DP

SINGLE COMPONENT READY TO USE POLYMER MODIFIER. DAMP PROOF COATING

Excellent water resistant. Exceptionally good for water-proofing with high bonding properties. UV resistant. Good crack bridging. COVERAGE: 1 Kg covers 5 to 6 Sq.m. at 100 microns thickness.

Classic ACRYFIX - L

A WATERPROOF ACRYLIC MODIFIER AND BONDING AGENT FOR CEMENTITIOUS

Developes excellent bond with most building material. Out-Standing water resistance. Reduces or prevents salt penetration into concrete. Good chemical resistance. Highly durable in continues wetting conditions. Increases flexibility. DOSAGE: 25 L mixed with neat cement for 50 kg cement; Normal plastering - 100 to 200 ml per bag of cement.

**Classic
SIL COAT**

SINGLE COMPONENT SILICONE BASED WATER REPELLENT COATING.

Provides a durable barrier to water penetration on porous surfaces ideal for exposed brickwork, Stone masonry and concrete blocks. Remains effective for many years. COVERAGE: 1 Lt. covers 6 to 8 Sq.mt.

REPAIRS ADHESIVE & SURFACE TREATMENTS

**Classic
RUST SHIELD**

SINGLE COMPONENT RUST CONVERTER, REMOVER.

Easy to use, brush applied rust converter or remover liquid for reinforcement steel and other rebar steel surfaces. COVERAGE: 1 Lt. will covers approx. 8 to 10 Sq.mt.

**Classic
COAT - RB**

POLYMER BASED PROTECTIVE ANTI-CORROSIVE COATING FOR STEEL AND REINFORCEMENT

Provides active corrosion protection for steel and reinforcement. Application by brush, roller or spray. Pre-weighted pack. Easy to apply. Excellent bond with steel and concrete. COVERAGE: 1 Kg pack covers 50 Kg of 12 mm diameter steel.

**Classic
PRIMECOAT**

PRIMER FOR CEMENTITIOUS REPAIRS.

Two part acrylic polymer based bonding agent for old to new concrete. Excellent bonding strength. COVERAGE: 1 Kg pack covers 3 to 4 Sq.mt.

**Classic
REPMATE**

PREPACKED CEMENTITIOUS REPAIR MORTAR STANDARDS: BS 6319 PART 2 1983 BS 6319 PART7 1985.

Designed for cost effective repairs to spalled or damaged concrete. Resists cracking and shrinkage. YIELD: 28 Kg per pack yields 11.1 litre.

**Classic
MICROMATE**

HIGH STRENGTH REPAIR MORTAR (MICRO CONCRETE).

Excellent adhesion with parent concrete positive grip with reinforcement, Efficient restoration material, Non shrink, attains high strength low permeability. Contains no corrosive substances. The repair can be done quickly without disturbing the surrounding. COVERAGE: 25 Kg + 4.25 Lt. water yield 13.5 Lt.

**Classic
CRACKMATE**

POLYMER CRACKMATE POLYMER MODIFIED CRACKFILLING MORTAR

Non shrink excellent crack filling ability, Smooth finish prevents further crack propagation. High tensile strength. COVERAGE: 1 Kg will cover approx. 15 to 25 Meters length of cracks cut into 6 mm deep V-groove.

**Classic
EPO BOND - 208**

EPOXY BONDING AGENT STANDARDS:BS 6319 PART 1983 BS 6319 PART

Two part prepacked epoxy bonding agent for old to new concrete. Can be applied on dump surface. Excellent bond strength. COVERAGE: 1 Kg pack covers 3 to 4 Sq.mt.

**Classic
EPO SEAL - 204**

FLEXIBLE, SOLVENT FREE, EPOXY ADHESIVE AND SEALANT.

A versatile, flexible, epoxy sealant designed specifically for use in building and construction. Suitable for filling saw cut joints and cracks. Tough abrasion and chemical resistance. COVERAGE: 3 Sq.mt. per Kg for bonding application.

**Classic
EPO MORTAR - 301**

TWO COMPONENT POLYESTER REPAIR MORTAR.

An economical, high strength two part fast setting repair compound. Easy to use Excellent chemical resistant. Resistant to water and weathering. YIELD: 1 Kg pack yield 0.5 liter.

**Classic
EPO PATCH - 302**

HIGH STRENGTH EPOXY PATCHING AND VOID FILLING COMPOUND

Excellent bonding with the substrate. No priming required does not shrink on curing and has excellent resistance to weathering and chemical attack. COVERAGE: 1 Kg pack covers 0.5 to 0.6 Sq.mt. with 20 mm depth.

**Classic
EPO PRIMER - 273**

EPOXY BASED SEALER AND SURFACE HARDENER.

Primer for epoxy coating on steel and concrete. Seals the concrete surface, colourless increased resistance through abrasion and chemical attack. COVERAGE: 5 to 7 meter square per litre for 2 coat.

**Classic
STRONG COAT
202AR**

HIGH BUILD SOLVENT FREE EPOXY COATING WITH OUTSTANDING CHEMICAL RESISTANCE.

Thixotropic Hard-wearing and hygienic coating for concrete and metal surfaces. Outstanding chemicals and acid resistance. COVERAGE: 5 Kg pack covers 7 to 9 Sq.mt. for 2 coats.

Classic
EPO - ETP 3

EPOXY TILE GROUT

Good chemical resistance. Available in different colours. Water resistant and stain proof.

Classic
CRETE - TA

A SINGLE COMPONENT CERAMIC TILE ADHESIVE SUITABLE FOR FIXING TILES ON CONCRETE, CEMENT OR LIME MORTARS.

Suitable for use in damp and totally submerged conditions. High bond strength good work and open wet times of 20 minutes at 35 degree C. COVERAGE: 25 Kg pack covers 5 to 8 Sq.mt.

Classic
CRETE - TT

A SINGLE COMPONENT TILE ADHESIVE SUITABLE FOR FIXING TILES ON STONES, GRANITE, INCLUDING TILES ON TILES

Good flexibility resists thermal movement can be used for external cladding of tiles and granite stone. Good bonding even on smooth surfaces. COVERAGE: 25 Kg pack covers 5 to 8 Sq.mt.

Classic
CRETE - TP

A SINGLE COMPONENT COLOURED GROUT USED FOR POINTING TILE JOINTS

Gives bonding suitable for use in wet conditions, no colour changes. Available in different colours.

Classic
CRETE
WALL PUTTY

POLYMER MODIFIED WALL PUTTY IN PASTE FORM FOR INTERIOR AND EXTERIOR

Excellent bonding to surface. Water resistant, self curing. COVERAGE: 1 Kg covers 3 to 4 Sq.mt. on smooth surface.

Classic
CRETE - MA

MARBLE ADHESIVE AND ADHESIVE FOR GLASS STONE.

Good flexibility resists thermal movement can be used for external cladding of marble and granite stone. Good bonding even on smooth surfaces. COVERAGE: 20 Kg pack covers 3.5 Sq.mt.

INDUSTRIAL GROUT & FLOORING

Classic
GROUTMATE 400

NON-SHRINK, FREE FLOW, HIGH STRENGTH CEMENTITIOUS GROUT

General purpose cementitious grout, ideal for static loads. High strength, non-shrink, free grout. YIELD: 25 Kg + 4.25 Lt. of water yields 13.0 Lt.

Classic
GROUTMATE 600

NON-SHRINK, FREE FLOW, ULTRA HIGH STRENGTH CEMENTITIOUS GROUT

Attains ultra-high strength, Ready to use. Freely flows under base plates and bolt packets. High early and ultimate strength. Ideal for dynamic loads. YIELDS: 25 Kg + 3.75 liters yields 12.8 litres.

Classic
GROUT ADMIX

SUPER PLASTICING, EXPANDING GROUT ADDITIVE

Produces non-shrink, free flowing and more cohesive grout. DOSAGE: 200g per 50 Kg cement.

Classic
ANCHORGROUT

POLYESTER REXIN ANCHOR-GROUT

Ultra-high compressive and pull out strength. Corrosion resistant. Can be used under water. Rapid setting. YIELD: 1 Kg yields 0.5 liters

Classic
STRONG
GROUT - 231

EPOXY REXIN GROUT

Flowable, Non-sink, attained high early and ultimate strength. Excellent chemical resistance, 3 part system. 12 Kg pack yield approx. 5 Lt.

Classic
FLOOR TOP - HD

HARD WEARING INDUSTRIAL HEAVY DUTY FLOOR SCREED.

Heavy duty traffic flooring. Non-metallic, non-dusty and non-slippery flooring system. Excellent abrasion and impact resistant. COVERAGE: 25 Kg covers 1 Sq.mt at 10 mm thick.

Classic
FLOOR TOP - HT

HARD WEARING INDUSTRIAL FLOOR TOPPING COMPOUND STANDARD: BS8204

Non-metallic, non-dusty and non-slippery flooring compound. Dry shake applied over fresh concrete to provide a monolithic floor. Ensures outstanding abrasion resistant. COVERAGE: 5 Kg covers 1 Sq.mt.

**Classic
FLOOR
TOP - HTL**

HARD WEARING INDUSTRIAL FLOOR
TOPPING COMPOUND

Non-metallic, non-dusty and non-slippery flooring compound. Dry shake applied over fresh concrete to provide a monolithic floor. Ensures high abrasion resistant. COVERAGE: 5 Kg covers 1 Sq.mt.

SEALANTS & PROTECTIVE COAT

**Classic
POLYSEAL**

TWO PART POLYSULPHIDE SEALANT
(GUN GRADE)

High resistance to climate extreme and physical damage. Good resistance to occasional spillage of dilute acids. Recommended for critical joint sealing and for sealing structural expansion joints. (Specific Gravity 1.6kg)

**Classic
ACRYSEAL**

ACRYLIC SEALANT

Forms a tough seal. Excellent adhesion to variety of substrates. Recommended for interior crack repair. Internal perimeter seals and internal walls & ceilings, wash basins and walls. Joint areas under totally dry conditions.

**Classic
TACCOAT**

PROTECTIVE DECORATIVE ANTI-CARBONATION COATING

Anti-carbonation properties. Allows surface to breathe. High degree of elasticity. Available in different colours. Totally water repellent. Protects against algae and fungi. 2 coats required for effective anti-carbonation. COVERAGE: 35 to 4 Sq.mt. per Kg for 2 coats.

**Classic
TACCOAT - TS**

PROTECTIVE WATERPROOFING,
THERMAL INSULATION COATING FOR
TERRACE AND WALLS

Allows surface to breath, High degree of elasticity, Waterproofing, High Thermal Insulation Property. COVERAGE: 1 Kg cover 3 to 3.5 Sq.mt.

**Classic
REMOULD**

MOULD RELEASE AGENT

Gives excellent surface finish. Economical and easy to use. No stains of oil on concrete surfaces. COVERAGE: 1 Lt. diluted with 5 Lt. of water covers 150-160 Sq.mt.

**Classic
REMOULD - RTU**

MOULD RELEASE AGENT

Gives excellent surface finish. Economical and easy to use. No stains of oil on concrete surfaces. COVERAGE: 1 Lt. covers 22-30 Sq.mt.

**Classic
EPO ZRP - 371**

TWO PART EPOXT BASED ANTI-CORROSIVE COATING

Optimum protection from corrosion. Provided by excellent adhesion to iron and steel. Can be applied by brush. COVERAGE: 1 Kg covers 35-45 Sq.ft.

**Classic
EPO WBE - 381**

TWO COMPONENT WATER BASED
EPOXY COATING

Develops high hardness and abrasion resistant with good viscous elasticity. Forms thick layer and withstand negative water pressure. COVERAGE: 1 Kg covers 4 to 5 Sq.mt.

**Classic
PU SEAL**

LOW MODULUS PU SEALANT

Sealing of expansion construction joints, sealing joints between bricks, tiles and granites sealing joints of metal container finish precast concrete panel.

**Classic
PU GROUT**

POLYURETHANE BASE PRESSURE
GROUT

Two component low viscosity moisture reactive polyurethane grouting systems. Excellent bond strength to concrete, brick work and masonry.

ECOFRIEDLY & SPECIAL PRODUCTS

**Classic
INSTACEM**

GEO POLYMER BASE REPAIR MORTAR

An extremely versatile, Cementitious, Rapid setting, Semi leveling structural repair concrete. Self curing and self priming.

**Classic
TECHNOFILL**

GEO POLYMER BASED CRACK FILLING
MORTAR

A Geo polymer based crack filling mortar with non-shrink properties. Prepared by adding the specified quantity of water to the powder.

BITUMEN PRODUCTS

Classic **INNOCOAT - BW**

BITUMEN WATERPROOFING AND
CHEMICAL RESISTANCE

Excellent bonding with building materials, Composed of bitumious phenolic modified high viscous with proper fine filler and additive suitable for water proofing and chemical resistance. COVERAGE: 1L cover 6 - 8 Sq.mt. Recommended 2 coat.

Classic **INNOCOAT - BAC**

BITUMEN ANTI-CORROSIVE BLACK
COATING AND CHEMICAL RESISTANCE

Excellent bonding with most building materials, based on a special type bitumen, containing phenolic resin. COVERAGE: 8 Sq.mt - per lit , recommended 2 coat.



OUR NETWORK

We hadn't just stopped in giving the quality product to our customer, we also extend in providing consultancy & services. In this view, Primadonn Buildtech Pvt. Ltd. provide the client with services across the country to satisfy our customer at most.

Our Supports around country are as follows.

Puducherry	-	Er. S. Mailavelu, B.E., (+91-9629660298)
Cuddalore	-	Mr. G. Elankumaran, (+91-9578181803)
Kumbakonam	-	Er. K. Mathiyalagan (+91-9443212285)
Mannarkudi	-	Er. R. Balamurugan, M.Tech., (+91-9443350271)
Vellore	-	Mr. Victor (+91-9443715080) [Victor Pavers]
Ullundurpettai	-	Mr. Annamalai (+91-9842220243) [A.B. Chemicals]
Tirupur	-	Mr. M. Gowrishankar (8508792737) [Classic Tiles]
Chennai	-	Mr. Thiayagarajan (+91-9500079065) [VPS Enterprises] - A.Sirajudeen (+91-9841091876) [Dural Trims & Profiles Pvt. Ltd.]
Madurai	-	Er. G.Mohan 9486111088
Coimbatore	-	Mr. Arulmurugan (+91-9363101020) [Murugan Arul Enterprises]
Auroville	-	Mr. D. Murugan (+91-9362856662)
Ahmedabad	-	Mr. Karthik Setiyar (+91-8238182167)
Hyderabad	-	Mr. Ferroze Chateliar(+91-9444052228)

To know more about information on our networks, log on to

www.primadonn.com/contactusall

or mail us to

networks@primadonn.com

www.primadonn.com



BASEMENT, RETAINING WALLS & CONCRETE EXPOSED TO SOIL.
CLASSIC ACRYBOND,
CLASSIC INNOCOAT - BW

CEILING FASTENERS, STAIRCASE FASTENER.
CLASSIC ANCHOR-GROUT
CLASSIC INSTACEM



EXTERIOR PAINT
CLASSIC TACCOAT
CLASSIC SILCOAT

FLOORING TILE FIXING
CLASSIC CRETE - TA,
CLASSIC CRETE - TP,
CLASSIC CRETE - MA,
CLASSIC EPO - ETP - 3



FOUNDATION M15, M20
CLASSIC SUPERFLO - N
CLASSIC SUPERFLO - SP

INTERIOR WALL
CLASSIC CRETE - WALL PUTTY,
CLASSIC TACCOAT



MASONRY & PLASTERING
CLASSIC POLYPROPYLENE,
CLASSIC MORTAR PLASTICIZER,
CLASSIC PLASTOMASTER



PILING M30, M35
 CLASSIC SUPERFLO - SP,
 CLASSIC SUPERFLO - SPECIAL

RCC BEAM & COLUMN
 CLASSIC SUPERFLO - SP,
 CLASSIC REMOULD



RCC SLAB
 CLASSIC CRETE - RMW,
 CLASSIC SUPERFLO - SP,
 CLASSIC CRETE - AXL (Slope Roof)

SUNKEN & BATHROOM
 CLASSIC RAPID SETPLUG, CLASSIC ACRYBOND,
 CLASSIC ACRYFIX - SB,
 CLASSIC CRETE - TA, CLASSIC - EOP - ETP - 3



SWIMMING POOL
 CLASSIC ACRYBOND A,
 CLASSIC TANKSCREED,
 CLASSIC CRETE - TA, CLASSIC - EPO - ETP - 3

WATER TANK & OPEN TERRACE
 CLASSIC ACRYBOND - A,
 CLASSIC TANKSCREED,
 CLASSIC ACRYFLEX - WMC



WINDOWS PANEL
 CLASSIC ACRYSEAL



PRIMADONN BUILDTECH Pvt. Ltd.

D/1, Sri Sai Apartments, Indian Airlines Colony,
Trimulgherry, Secunderabad-500015 (AP)
Mob.No: +91-9444052228.

No. 349, First Floor, RS Road, Srinivasa Nagar,
Kavaraipettai, Gummidipoondi. chennai-601206
Mob.No- +91-9444907177

No.151, Chinna Subbraya Pillai Street, Pondicherry.
Mob.No: +91- 9345561820

Manufacturing Unit

YASH CONCHEM Pvt. Ltd., 877/2 Lotus Colony, 3rd Street,
Thattankulam Road, Madhavaram, Chennai-600060,
Phone: 044-25530796 Mob.No: +91-9962049994

DEALERS AND DISTRIBUTORS

To get more information about our products and updates, please
mail us to info@primadonn.com (or) log on to www.primadonn.com

