



CLASSIC FIBTM PPF

Synthetic Fibre for Construction

Product:

Classic Fib PPF fibres of around 12mm length with unique triangular cross section for easy dispersion in concrete mix.

Description:

Classic Fib PPF fibres consists of polypropylene fibres of around 12 mm length with unique triangular cross section. **Classic Fib PPF** improves the various physical properties of cement concrete and mortar plaster. It increases the compression, tensile and flexural strength by 5 % to 10 %. It controls thermal and surface cracks caused by volume change and consequently decreases water permeability. It reduces wastage of plaster due to rebound. It also increases adrasion resistance of concrete.

Purpose & Uses:

Used as an admixture for cement and mortar/plaster to improve its working and application properties. Eliminates use of chicken mess/weld mesh in plastering applications.

Pack & Dosage:

Available only in 125 gm pack which can be used for 50 KG bag of cement.

Properties:

Classic Fib PPF has excellent dispersion property with excellent acid resistance and good alkali resistance. It is environmental friendly and non-hazardous.

Advantages:

- Easy dispersion in the mix.
- Crack inhibition
- Increased tensile strength
- Decreased water permeability
- Less shrinkage
- Less wastage
- Non-Toxic
- Environmental Friendly

Introduction to Use:

Classic Fib PPF fibres is added to the cement concrete/mortar in the mixer along with concrete/mortar at a specified dosage of 125 gm per 50 Kg of cement and mixed well for 3-4 minutes. In case of manual mixing, it is soaked in gauging water for 2-3 minutes and this water is poured over the mortar and mixed well for best results.

Variety of Products:

Following are other similar products from Primadonn Buildtech Pvt Ltd.,

- Classic Airent
- Classic Airent-3
- Classic Crete-AXL (CB)
- Classic Crete-AXL (CF)
- Classic Crete-RMW (Powder)
- Classic Crete-RMW
- Classic Crete RPL
- Classic Mortar Plasticizer
- Classic Plasto-Master
- Classic Superflo-PC
- Classic Superflo-N
- Classic Superflo-SP
- Classic Superflo Special

CLASSIC FIBTM PPF

Synthetic Fibre for Construction



TAMILNADU

Corporate Office

PRIMADONN BUILDTECH PVT LTD

No. 349, First Floor, Srinivasa Nagar, Kavaripeetai, Gummidipoondy 601 206.

Ph+91-8220513172,

Admin Office:

No.605, Selva Vinayaga Nagar, Grant Lyon Village, Ponneri Tk., Thiruvalluvar Dt., Ph+91-6379174327, +91-8438276059.

Manufacturing Unit

No.603, Selva Vinayaga Nagar, Grant Lyon, Vadagarai, Chennai 600 052. Ph.+91-9444907177

KARNATAKA

Corporate Office:

PRIMADONN CONSTRUCTION CHEMICALS (P) LTD.,

Talacauvery Layout, Basavanagar, Bangalore 560 037. Ph.+9150878429, +91-9345411355.

PONDICHERY

Branch Office

192/A, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-4208833, 91-+9514709240

Distributor's

151, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-2222100, 91-+9345561820

Email: Info@Primadonn.com, www.Primadonn.com

