



CLASSIC DURA CRACKMATE HD

Two Part System

Product:

A factory blended easy to use, polymer modified, high strength, non-shrink, cementitious crack filling mortar. Designed for cost effective filling of cracks in concrete, masonry and plaster surfaces including shrinkage cracks in plaster.

Description:

Classic Crackmate HD is a polymer modified cementitious crack filling mortar with non-shrink properties, prepared by adding the specified quantity of water to the powder. **Classic Crackmate HD** is used special crack to fill cracks in both interior and exterior concrete, masonry and plaster surfaces. It can also be used as a thin render to even out surfaces.

Advantages & Benefits:

- Non-Shrink mortar with Strong adhesive properties.
- Excellent crack filling ability.
- Smooth finish.
- Prevent further crack propagation.
- High tensile strength.

Pack & Coverage:

Available in 0.5 & 1 Kg packs. 1 Kg will fill approx. 30-40m length of cracks cut into 6 mm deep V-groove.

Instructions for Use:

Surface Preparation:

Cut the cracks into 6mm deep V-grooves. Clean the grooves with a brush to remove all loose particles. Sprinkle grooves with clean water.

Storage Life

Classic Crackmate HD has a shelf life of 6 months when stored, unopened in the original pack, under dry condition at moderate temperatures.

Mixing:

Classic Crackmate HD preferably mixed mechanically using a slow speed drill with paddle attachment, slowly adding 0.2 Kg of Classic Crackmate HD Liquid until a homogenous mortar of smooth, creamy and trowellable consistency is obtained.

Application:

Fill the prepared cracks tightly with the mortar using a small trowel or putty blade and finish to a level surface. Remove excess mortar with clean moist sponge or soft cloth before it dries totally.

Handling Precautions:

Classic Crackmate HD is non-toxic, but mildly alkaline when wet. However, in its wet state. If contact with skin occurs, wash well with clean water. Inhalation of dust from the dry material should be avoided.

Storage Life

Classic Crackmate HD has a shelf life of 6 months when stored, unopened in the original pack, under dry condition at moderate temperatures.

Variety of Products:

Following are the other similar products from Primadonn Buildtech Pvt. Ltd.,

- Classic Coat - RB
- Classic Cure-C
- Classic Epoxy Mortar - 301
- Classic Epoxy Patch-302
- Classic Epoxy Primer -273
- Classic Epoxybond – 208
- Classic Epoxyseal-204
- Classic ETP-3
- Classic Epoxyseal-204
- Classic ETP - 3

CLASSIC DURATM CRACKMATE HD

Two Part System



TAMILNADU

Corporate Office

PRIMADONN BUILDTECH PVT LTD

No. 349, First Floor, Srinivasa Nagar, Kavaripeetai, Gummidipoondy 601 206.

Ph+91-8220513172,

Admin Office:

No.605, Selva Vinayaga Nagar, Grant Lyon Village, Ponneri Tk., Thiruvallur Dt., Ph+91-6379174327, +91-8438276059.

Manufacturing Unit

No.603, Selva Vinayaga Nagar, Grant Lyon, Vadagarai, Chennai 600 052. Ph.+91-9444907177

KARNATAKA

Corporate Office:

PRIMADONN CONSTRUCTION CHEMICALS (P) LTD.,

Talacauvery Layout, Basavanagar, Bangalore 560 037.
Ph.+9150878429, +91-9345411355.

PONDICHERRY

Branch Office

192/A, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-4208833, 91-+9514709240

Distributors

151, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-2222100, 91-+9345561820

Email: Info@Primadonn.com, www.Primadonn.com

