



CLASSIC CRETE TACCOAT PREMIUMTM

Protective and Anti Carbonating Coating

Product:

A high-build micro porous coating with excellent resistance to attack by carbon dioxide, air borne chlorides, acid rain with exceptional weathering characteristics.

Advantages & Benefits

- Anti-Carbonate Properties
- Excellent weathering properties
- Gap bridging properties
- Allows substrate to breathe.
- Excellent bond and Anti Fungus
- Choice of colours.
- Excellent water repellence
- Single pack, brush applied.
- Forms flexible film.
- Nontoxic / Non-inflammable

Purpose:

To provide a smooth decorative durable coating for concrete and masonry surfaces. Two coat applications are recommended.

Packing:

1,2,5,7,12,25 Kg Containers.

Coverage:

Classic Taccoat Premium will cover Approx. 3 to 4 Sq.mt./Kg/two coats (depends on substrate texture).

Description:

Classic Taccoat Premium is ready to use elastomeric aqueous based coating containing special polymers and fillers. **Classic Taccoat Premium** provides extremely tough protective decorative coating that allows surface to breathe.

Uses:

Classic Taccoat Premium has been specially designed for the decoration and protection of concrete against attack from atmospheric carbon dioxide, airborne chlorides, acid rain, weathering, etc.,

Properties:

Classic Taccoat Premium is non-inflammable and hence can be used for interiors also. **Classic Taccoat Premium** has excellent adhesion to the substrate and cures to form a flexible film that allows the surface to breathe and acts as carbon dioxide barrier thus protecting the concrete in aggressive weather conditions. It has excellent gap bridging ability and does not age with time and forms an extremely durable film.

Typical Properties:

Specific Gravity-----	1.38
Surface finish-----	Matt
Fire Resistance -----	Non-inflammable
Application Temperature-----	3-40 °C
Drying Time-----	30 minutes at 30 °C
Touch Dry-----	4 hours at 30 °C
Thorough Dry-----	12 Hours

How to Use:

Surface Temperature:

Substrates must be clean, sound and free from dust and loose particles . All holes and cracks must be filled with suitable filler. All traces of oil ,grease or other contamination must be removed. The new concrete surface must be at least 14 days old before coating. If in doubt allow full curing to take place for 28 days before application of **Classic Taccoat Premium**.

Priming with Classic Taccoat Premium :

On old or porous surfaces, ensure that the substrate is sound. Dilute 2 parts of **Classic Taccoat Premium** with 1 part of water and prime the surface. When it is tacky or touch dry (i.e after 1/2 to 3 hours) apply **Classic Taccoat Premium** on the primed surface, as final coat diluting **Classic Taccoat Premium** with the water 33% to 50 % depending upon the ambient temp.

Priming coat-water 33%

Final coat- water 10% to 20%

Application:

Stir the material in the container thoroughly and mix water as per the site requirement spread evenly with a brush, roller or airless spray. Avoid application during rainy, weather . In hot, dry, weather , dampen unpainted surfaces with water to prevent **Classic Taccoat Premium** drying too rapidly.

CLASSIC CRETETM TACCOAT PREMIUM

Protective and Anti Carbonating Coating

Colours:

Available in 25 different shades .

Cleaning :

Tools should be cleaned immediately after use with water.

Storage:

Can be stored for 12 months. **Classic Taccoat Premium** should be stored unopened and protected from heat .

Variety of products:

- Classic Acryseal
- Classic polyseal
- Classic PU Grout
- Classic PU Seal
- Classic Remould
- Classic Remould -RTU
- Classic Taccoat Premium-TS
- Classic ZRP-371



TAMILNADU

Corporate Office

PRIMADONN BUILDTECH PVT LTD

No. 349, First Floor, Srinivasa Nagar, Kavaripettai, Gummidipoondy 601 206.

Ph+91-8220513172,

Admin Office:

No.605, Selva Vinayaga Nagar, Grant Lyon Village, Ponneri Tk., Thiruvallur Dt., Ph+91-6379174327, +91-8438276059.

Manufacturing Unit

No.603, Selva Vinayaga Nagar, Grant Lyon, Vadagarai, Chennai 600 052. Ph.+91-9444907177

KARNATAKA

Corporate Office:

PRIMADONN CONSTRUCTION CHEMICALS (P) LTD.,

No.603, Selva Vinayaga Nagar, Grant Lyon, Vadagarai, Chennai 600 052. Ph.+91-9444907177

KARNATAKA

Corporate Office:

PRIMADONN CONSTRUCTION CHEMICALS (P) LTD.,

Talacauvery Layout, Basavanagar, Bangalore 560 037. Ph.+9150878429, +91-9345411355.

PONDICHERRY

Branch Office

192/A, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-4208833, 91-+9514709240

Distributor's

151, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-2222100, 91-+9345561820

Email: Info@Primadonn.com, www.Primadonn.com

